

Aufsetzpuffer aus AUTAN® HE

Lieferprogramm und Einsatzbereiche

nach DIN EN 81-20/50 bei Nenngeschwindigkeit bis 1,00 m/s



Lieferprogramm			Baumusterprüfbescheinigung	Zulässige Einsatzbereiche [kg]				Abmessungen [mm]							
D × H	Typ	Art.-Nr.	Registrier-Nr.	bis v = 0,63 m/s		bis v = 1,00 m/s		D	d	d ₁	H	s	L	L ₁	d ₂
				m _{min}	m _{max}	m _{min}	m _{max}								
80 × 80	A	300400L1	44 208 17053401	140	1650	230	750	80	36	17,0	80	5	100	80	11
	C	300400L3								18,0		6			
	D	300400L4								17,2		2			
100 × 80	A	300401L1	44 208 17053403	240	3500	350	1200	100	36	17,0	80	5	130	100	14
	C	300401L3								18,0		6			
	D	300401L4								17,2		2			
100 × 80	A	300401M1	44 208 17053402	200	2100	250	950	100	36	17,0	80	5	130	100	14
	C	300401M3								18,0		6			
	D	300401M4								17,2		2			
125 × 80	A	300402L1	44 208 17053404	450	5500	620	1900	125	36	17,0	80	5	155	125	14
	C	300402L3								18,0		6			
	D	300402L4								17,2		2			
140 × 80	A	300419L1	44 208 17053405	450	6500	700	2300	140	36	17,0	80	6	180	140	18
	C	300419L3								18,0		6			
	D	300419L4								17,2		2			
165 × 80	A	300403L1	44 208 17053406	600	9400	1000	2800	165	36	17,0	80	5	205	165	18
	C	300403L3								18,0		6			
	D	300403L4								17,2		2			
220 × 80	A	300404L1	44 208 17053407	1000	9400	1400	5500	220	36	17,0	80	5	260	220	21
	C	300404L3								18,0		6			
	D	300404L4								17,2		2			
81 × 120	A	300335A1	44 208 12019089-001	-	-	230	900	81	36	17,0	120	5	100	80	11
	C	300335A3								18,0		6			
	D	300335A4								17,2		2			
101 × 163	A	300405A1	44 208 12019092-001	-	-	300	1600	101	36	17,0	163	5	130	100	14
	C	300405A3								18,0		6			
	D	300405A4								17,2		2			
129 × 103	A	300178A1	44 208 12019094-001	-	-	600	2100	129	36	17,0	103	5	155	125	14
	C	300178A3								18,0		6			
	D	300178A4								17,2		2			
142 × 101	A	300183A1	44 208 12019096-001	-	-	700	2200	142	36	17,0	101	6	180	140	18
	C	300183A3								18,0		6			
	D	300183A4								17,2		2			